

# DH-SD22404T-GN-W

4MP 4x PTZ Wi-Fi Network Camera



- 1/3" 4Megapixel CMOS
- Powerful 4x optical zoom
- WDR, Day/Night(ICR), Ultra DNR
- Max. 25/30fps@4M/3M
- IVS
- Support Wi-Fi
- IP66, IK10



## System Overview

Featuring powerful optical zoom and accurate pan/tilt/zoom performance, the camera provides a wide monitoring range and great detail. The camera delivers 4MP resolution at 25/30fps. The camera is equipped with smooth control, high quality image, and good protection, meeting compact size demands of video surveillance applications.

## Functions

### Wide Dynamic Range

The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, True WDR (120 dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

### High Efficiency Video Coding (H.265)

The H.265 (ITU-T VCEG) video compression standard offers double the data compression ratio at the same level of video quality, or substantially improved video quality at the same bit rate, as compared to older video compression technologies. H.265 offers such impressive compression by expanding the pattern comparison and difference-coding, improving motion vector prediction and motion region merging, and incorporating an additional filtering step called sample-adaptive offset filtering.

## Environmental

Dahua cameras operate in extreme temperature environments, rated for use in temperatures from -30 °C to +60 °C (-22 °F to +140 °F) with 95% humidity. The camera complies with the IK10 Vandal Resistance impact rating. Subjected to rigorous dust and water immersion tests and certified to the IP66 Ingress Protection rating makes it suitable for demanding outdoor applications.

## Interoperability

The camera conforms to the ONVIF (Open Network Video Interface Forum) specifications, ensuring interoperability between network video products regardless of manufacturer.

Technical Specification				IVS	Tripwire, Intrusion, Abandoned/Missing
Camera				Advanced Intelligent Functions	Face Detection
Image Sensor	1/3" CMOS			Video	
Effective Pixels	2592(H) x 1520(V), 4 Megapixels			Compression	H.265/H.264
RAM/ROM	256M/128M			Streaming Capability	3 Streams
Electronic Shutter Speed	1/1s~1/30,000s			Resolution	4M(2592×1520)/3M(2304×1296)/1080P(1920×1080)/720P(1280×720)/D1(704×576/704×480)/CIF(352×288/352×240)
Scanning System	Progressive				Main stream: 4M/3M/1080P/1.3M/720P (1~25/30fps)
Minimum Illumination	Color: 0.05Lux@F1.6; B/W: 0.005Lux@F1.6			Frame Rate	Sub stream1: D1/CIF(1 ~ 25/30fps)
S/N Ratio	More than 50dB				Sub stream2: 720P/D1/CIF (1~25/30fps)
IR Distance	N/A			Bit Rate Control	CBR/VBR
IR On/Off Control	N/A			Bit Rate	H.265/H.264: 448K ~ 8192Kbps
IR LEDs	N/A			Day/Night	Auto(ICR) / Color / B/W
Lens				Backlight Compensation	BLC / HLC / WDR (120dB)
Focal Length	2.7mm~11mm			White Balance	Auto, ATW, Indoor, Outdoor, Manual
Max. Aperture	F1.6 ~ F2.8			Gain Control	Auto / Manual
Angle of View	H: 112.5° ~ 30°			Noise Reduction	Ultra DNR (2D/3D)
Optical Zoom	4x			Motion Detetion	Support
Focus Control	Auto/Manual			Region of Interest	Support
Close Focus Distance	100mm~ 1000mm			Electronic Image Stabilization (EIS)	N/A
DORI Distance				Defog	Support
*Note: The DORI distance is a "general proximity" of distance which makes it easy to pinpoint the right camera for your needs. The DORI distance is calculated based on sensor specification and lab test result according to EN 62676-4 which defines the criteria for Detect, Observe, Recognize and Identify respectively.				Digital Zoom	16x
Detect	Observe	Recognize	Identify	Flip	180°
180m(591ft)	72m(236ft)	36m(118ft)	18m(59ft)	Privacy Masking	Up to 24 areas
PTZ				Network	
Pan/Tilt Range	Pan: 0° ~ 355°; Tilt: 0° ~ 90°			Ethernet	RJ-45 (10XBase-T/100Base-TX)
Manual Control Speed	Pan: 0.1° ~100° /s; Tilt: 0.1° ~60° /s			Wi-Fi	Wi-Fi(IEEE802.11a/b/g/n/ac) , 2.4G Wi-Fi
Preset Speed	Pan: 100° /s; Tilt: 60° /s			Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS,PPPOE,DDNS,FTP, IP Filter, QoS, Bonjour, 802.1x
Presets	300			Interoperability	ONVIF Profile S&G, API
PTZ Mode	5 Pattern, 8 Tour, Auto Pan ,Auto Scan			Streaming Method	Unicast / Multicast
Speed Setup	Human-oriented focal Length/ speed adaptation			Max. User Access	20 users
Power up Action	Auto restore to previous PTZ and lens status after power failure			Edge Storage	NAS (Network Attached Storage), Local PC for instant recording, Micro SD card 256GB
Idle Motion	Activate Preset/ Scan/ Tour/ Pattern if there is no command in the specified period			Web Viewer	IE, Chrome, Firefox, Safari
Protocol	DH-SD			Management Software	Smart PSS, DSS, DMSS
Intelligence				Smart Phone	IOS, Android
Event Trigger	Motion detection, Video tampering, Network disconnection, IP address conflict, Illegal access, Storage anomaly			Certifications	
Auto Tracking	N/A			Certifications	CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB,ANSI C63.4-2014 UL: UL60950-1+CAN/CSA C22.2, No.60950-1

Interface

Video Interface	N/A
RS485	N/A
Audio I/O	N/A
Alarm I/O	N/A

Electrical

Power Supply	DC 12V/1.5A
Power Consumption	10W

Environmental

Operating Conditions	-30°C ~ 60°C (-22°F ~ +140°F) / Less than 95% RH
Ingress Protection	IP66
Vandal Resistance	IK10

Construction

Casing	Metal
Dimensions	Φ122 (mm) x 89 (mm)
Net Weight	0.66kg(1.46lb)
Gross Weight	0.71kg(1.57lb)

Ordering Information

Type	Part Number	Description
4MP PTZ Camera	DH-SD22404T-GN-W	4MP 4x PTZ Wi-Fi Network Camera, WDR, PAL
	DH-SD22404TN-GN-W	4MP 4x PTZ Wi-Fi Network Camera, WDR, NTSC
	SD22404T-GN-W	4MP 4x PTZ Wi-Fi Network Camera, WDR, PAL
	SD22404TN-GN-W	4MP 4x PTZ Wi-Fi Network Camera, WDR, NTSC
Accessories	PFA137	Mount Adapter
	DC12V/2A	Power Adapter
	PFB203W	Wall Mount
	PFB200C	In-ceiling Mount
	PFA152-E	Pole Mount

Accessories

Optional:



PFA137  
Mount Adapter



DC12V/2A  
Power Adapter






PFB203W  
Wall Mount



PFA152-E  
Pole Mount



PFB200C  
Ceiling Mount

Wall Mount	Pole Mount
PFB203W	PFB203W + PFA152-E
	
	
<b>Junction Box Mount</b>	
	

Dimensions (mm)

